

Account Number	Date	Full Patient Name / Reference Number
-----------------------	-------------	---

Account Name	Ship To Acct
---------------------	---------------------

LENS TYPE *All Lenses come standard with Super Hard Coating

	CLEAR	SENSITY	70% TINTING		VP MULTICOAT	POLARISED 85%	TRANSITIONS
Phoenix NuPolar Single Vision						Grey	
Phoenix Single Vision		Grey	Grey	Green			
Phoenix Summit CD (PAL)		Grey	Grey	Green			
Phoenix Summit PRO (PAL)		Grey	Grey	Green			
Phoenix iD Lifestyle (PAL)		Grey	Grey	Green			
Phoenix Trueform CD (PAL)		Grey	Grey	Green			
Phoenix Trueform PRO (PAL)		Grey	Grey	Green			
Phoenix Bifocal			Grey	Green			
Poly-Progressive		Grey				Grey	

PRESCRIPTION Power range restrictions apply to HOYA's safety lens range. Check with Customer Service or HOYA Safety Product Guide for further information

	Sph	Cyl	Axis	Prism 1	Prism 2
R					
L					
	Dist PD	Near PD	Addition	Eye Point	Seg Height
R					
L					

FRAME TYPE

CO safety 108 52-18 and 54-18	OnGuard 220 58-15, Black, Brown, Clear, Grey/Pink or Purple/White	Ugly Fish Warhead 58-15, Matte Black, Gloss Black or Grey
CO safety 200 52-18 and 54-18	OnGuard 220 55-15, Black, Brown, Clear, Grey/Pink or Purple/White	Ugly Fish Flame 55-18, Matte Blk, Gloss Blk, Brown, Tortoiseshell
CO safety 202 50-20, 52-20, 54-20 & 56-20	Matador Mojo 56-21, Matt Blk, Blk/Red, Silver, Blue/Silver or Tort	C-Safe 003 54-18, Gunmetal
CO safety 207 52-16, 54-16 and 56-18	Matador Katalina 56-16 Brown, Tort, Matte Blk or Smoke	C-Safe Velocity 55-16, Black
Ugly Fish Slim 46-30, Black	Matador Loco 56-21, Black or Crystal	Ugly Fish Twister 54-15, Gloss Blk, Brown or Red
Ugly Fish Glide 46-30, Black	Matador Rio 57-16, Black/Blue, Black/Grey, Black/Orange, Black/Red or Black/Yellow	Ugly Fish Robot 55-16, Black or Clear
Ugly Fish Ultimate 46-30, Black	Ugly Fish Cannon 59-15, Matt Black or Gloss Black	Ugly Fish Whirlwind 51-18, Grey, Gloss Black or Navy
Ugly Fish Cruise 46-30, Black		

EYE SIZE	BRIDGE SIZE	FRAME/LENS COLOUR
-----------------	--------------------	--------------------------

Special Instructions

PRINT **RESET** **SUBMIT**